

---

<b>Product name</b>	:	<b>MoTip Copper Spray</b>
<b>Article number</b>	:	<b>090301</b>
<b>Supplier / Producer</b>	:	<b>MOTIP DUPLI B.V.</b> <b>Wolframweg 2</b> <b>NL-8471 XC WOLVEGA</b> <b>Telephone number</b> <b>+31 561 – 69 44 00</b> <b>Telefax number</b> <b>+31 561 – 69 44 31</b>

---

### Product description

High quality spray with a high copper content to prevent wear and sticking of screwed connections which are exposed to very high temperatures.

### Applications

Brake parts  
Exhaust parts  
Screwed connections, which are exposed to high temperature  
Battery Poles  
Thread of Spark Plugs

### Product characteristics

High thermal stability  
Resistant to chemicals and weather influences  
Corrosion preventive  
Excellent adhesion  
Prevents wear and sticking  
Simplifies the future removal  
Directed jetspray

### Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	EP Grease and small copper particles
VOC-content	:	Approximately 69% w/w
Solid content	:	Approximately 31% w/w
Colour	:	Copper
Scent	:	Characteristic
Appearance	:	Paste
Relative density at 20°C	:	0,767 g/ml
Yield	:	1,26 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
Temperature resistant	:	-40°C to +1.100°C



### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C.  
Before use, shake the aerosol.

Apply copper spray. The specific lubrication property is achieved after evaporation of the solvent (approximately 1 minute).